

RAYMOND MODEL 510T

MODEL	RAYMOND MODEL: 510T (TILT-DECK)
GVWR	2990 Lbs.
WIDTH	INSIDE BED: 58.5 INCHES OUTSIDE BED: 60 INCHES
LENGTH	INSIDE BED: 119.0 INCHES OUTSIDE BED: 120.5 INCHES
TRAILER FRAME	MAIN FRAME: 3" X 2" X 3/16" A-36 ANGLE CROSS MEMBERS: 3" X 2" X 3/16" A-36 ANGLE SIDE STAKES: 2" X 2" X 3/16" A-36 ANGLE
TRAILER SIDES	STANDARD: 20" TALL (3-BOARD) 5/4" X 6" TOP CHOICE PRESSURE TREATED OPTIONAL: 27" TALL (4-BOARD) 5/4" X 6" TOP CHOICE PRESSURE TREATED
TONGUE & COUPLER	TRIPLE TONGUE: 2-1/2" X 2-1/2" X 11 GAUGE SQUARE TUBING TONGUE BRACES: 2" X 2" X 3/16" ANGLE 2-INCH 3500# CLASS 2 COUPLER
DECK	2" x 8" TOP CHOICE PRESSURE TREATED LUMBER
AXLE	(1) DEXTER D-35 3500# AXLE WITH 5 ON 4.50 BOLT PATTERN
SPRINGS	(2) DEXTER 1750# DOUBLE EYE SPRINGS (COMB. WEIGHT RATING: 3500#)
WHEELS	DEXSTAR MINI-MODULAR BOLT PATTERN: 5 ON 4.50 COLOR: SILVER
TIRES	14" or 15" KENDA LOADSTAR TRAILER TIRES SIZE: ST205/75D15
FENDERS	16 GAUGE HRCQSCS FORMED STEEL EZ REPLACE BOLT-ON
PAINT	VALSPAR PREMIUM QUALITY OIL-BASED ENAMEL APPLIED OVER VALSPAR RUST INHIBITIVE PRIMER
LIGHTING (LED)	DOT APPROVED LED LIGHTING WITH 4-PIN FLAT ELECTRICAL CONNECTOR AND HEAVY DUTY TAIL LIGHT GUARDS AND BRACKETS ARE STANDARD
OTHER	MANUAL TILT-DECK WITH PRESSURE TREATED SLIDE OUT LIFT GATE

*SPECIFICATIONS SUBJECT TO CHANGE PERIODICALLY WITHOUT NOTICE.